



## Blueeye Keyfob Hitag S

<b>IC type:</b>	R/W 256 bits	R/W 2048 bits	
<b>Physical:</b>	Thickness:	6.80 mm	± 0.50 mm
	Length:	47.40 mm	± 0.50 mm
	Width:	28.60 mm	± 0.50 mm
	Weight:	4.70 g	± 0.50 g
	Color:	Transparent Blue	
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Material:</b>	Polycarbonate.		
<b>Thermal:</b>	-30°C and + 80°C		
<b>Immersion:</b>	Water IP 67 (IEC 60529)		
<b>Mechanical:</b>	Drop test 10 times 10 cycles (1.8m)		
<b>Resistance:</b>	The Keyfob is designed to resist common stress known from access control and time and attendance systems.		
<b>Specials:</b>	The Keyfob is delivered on boxes of 100 pieces.		
<b>Parts number:</b>	<b>623910</b> for the 256 bits <b>624910</b> for the 2048 bits		
<b>Remark:</b>	More details are available on Philips' Hitag S specification		<a href="http://www.semiconductors.philips.com/markets/identification/">http://www.semiconductors.philips.com/markets/identification/</a>

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.  
 CLF 3.3.2.39 - V1 - 25.08.2003 - Released - DefKey : 10418

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL [info@sokymat.ch](mailto:info@sokymat.ch), WEB [www.sokymat.com](http://www.sokymat.com)