



Clamshell Card Hitag S

IC type:	R/W 256 bits	R/W 2048 bits	
Physical:	Thickness:	1.60 mm	± 0.40 mm
	Length:	85.80 mm	± 0.40 mm
	Width:	54.00 mm	± 0.40 mm
	Weight	7.80 g	± 0.50 g
	Color:	White	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz
Material:	Hard shell: = ABS; Cover foil: = PVC.		
Thermal:	- 35°C to +65°C		
Resistance:	The card is designed to resist common stress known from access control and time attendance systems.		
Specials:	For volume of > 50K pieces the cards could be ordered with a customized printing on the back side foil. For volume of >250K a customized logo could be embossed in the cover shell.		
Parts number:	623403 for the 256 bits 624403 for the 2048 bits		
Remark:	More details are available on Philips' Hitag S specification		http://www.semiconductors.philips.com/markets/identification/

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.32 - V1 - 22.08.2003 - Released - DefKey : 10410

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com