



## Epoxy Keyfob UNIQUE

<b>Description</b>	<b>Proximity Keyfob design to suit to most 125 kHz proximity systems.</b>		
<b>IC type:</b>	EM4102 64 bits RF/64 ASK Manchester		
<b>Physical:</b>	Thickness:	1.6	± 0.20 mm
	Width:	30 mm	± 0.20 mm
	Length:	45 mm	± 0.20 mm
	Color:	Black	
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Material:</b>	Epoxy		
<b>Storage temp:</b>	-40°C to 95 °C		
<b>Operating temp:</b>	-40°C to 85 °C		
<b>Immersion:</b>	Water IP 65		
<b>Mechanical:</b>	Drop test 10 times 10 cycles (1.8m)		
<b>Resistance:</b>	The Keyfob is designed to resist common stress known from access control and time and attendance systems.		
<b>Specials:</b>	The Keyfob is delivered on bags of 250 pieces		
<b>Part number:</b>	<b>K4102-030001 or 601140</b>		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.  
CLF 3.3.2.46 - V1 - 05.10.2004 - Released - DefKey : 11759

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com