



ID BAND

DRAFT

Chip type:	Mifare 1K – ISO 14443A Q5 – R/W 256Kbits UNIQUE – read only 64bits		
Physical:	Strap width	16 mm	
	Strap thickness:	1.5 mm	
	Strap length :	235 mm [to be updated]	
	Material:	Strap in TPE-E shore hardness D20 Housing and Buckle in PC	
	Color:	to be defined [Blue samples already available]	
Electrical:	Operating frequency:	125 kHz ± 6 kHz 14.5 MHz ± 0.75 MHz (for Mifare 1K)	* At room temperature
Chemical:	Water immersion IP67		* 20°C, 35min, 1m
Thermal:	Storage:	-25°C to +80 °C	
	Operating:	-25°C to +100 °C	
Printing:	Upon request on the strap either on the buckle		
Part number:	607045 with Mifare 1K 612045 with Q5 601045 with read only 64bits		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.56 - V1 - - - In Process - DefKey : 12281

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com