

## Preliminary Data Sheet



### Inline UHF Tag - EM4222 / 869MHz

<b>Chip type:</b>	EM4222 v2 – read only 64bits		* Test conditions and remarks
<b>Physical:</b>	Length:	230 mm ± 2 mm	
	Thickness:	15 mm ± 0.5 mm	
	Width::	15 mm ± 0.5 mm	
	Material:	PC+ABS Hi impact	
	Color:	Light grey	
<b>Electrical:</b>	Operating frequency:	869 MHz	*At room temperature
<b>Chemical:</b>	Water immersion IP 67		*20°C, 35min, 1m
	Resistant to mineral acids and to large number of organics acids aqueous saline solution		
<b>Thermal:</b>	Storage:	-40°C to +85°C	* 1x 1000h
	Peak:	+120°C	* 1x 1h
	Operating:	-20°C to +60°C	
<b>Part number:</b>	633902		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.  
CLF 3.3.3.90 - V1 - 07.02.2005 - Released - DefKey : 11888

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com