



LOGI TAG 120 Q5

Chip type:	Q5 – 264 bits R/W		* Test conditions and remarks
Physical:	Diameter:	12.4 mm ± 0.2 mm	
	Thickness:	2.0 +0.4/-0mm	
	Weight:	0.6 g	
	Material:	PPS + Epoxy	
	Color:	Black	
Electrical:	Operating frequency:	125 kHz ± 6 kHz	* At room temperature
Chemical:	Water immersion IP68		* 20°C, 24h, 1m
	Aqueous solution of salts,		* 20°C, 100 h
	Unleaded gasoline, Petroleum, motor oil		* 20°C, 100 h
	HCL (10%), bleach, formic acid (PH7), caustic soda (PH11)		* 20°C, 100 h
Mechanical:	Axial compression strength	800 N	* 10s
	Radial compression strength	500 N	* 10s
	Vibration	IEC 68.2.6	* 10 g, 10...2000 Hz, 3 axis, 2.5 h
	Shock	IEC 68.2.29	* 40 g, 6 ms, 6 axis, 2000 times
Thermal:	Storage:	-40°C to +130 °C	* 1x 1000h
		+160 °C	* 1x 35h
	Shock/fatigue:	-20°C to +160 °C	* 100x 10min with transposition in 30s
	Operating:	-25°C to +85°C	
Part number:	612115		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.3.52 - V3 - 07.11.2003 - Released - DefKey : 10871

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com