



TEAR SHAPE Hitag 1

Chip type:	HITAG 1 – 1kbit R/W		* Test conditions and remarks
Physical:	Width:	31 mm ± 0.3 mm	
	Length:	40 mm ± 0.3 mm	
	Thickness:	4.8 mm ± 0.3 mm	
	Material:	Polycarbonate	
	Color:	Black, red, blue	
Electrical:	Operating frequency:	125 kHz ± 6 kHz	* At room temperature
Chemical:	Water immersion IP67		
Thermal:	Storage:	-25°C to +80°C	* 1x 1000h
	Operating:	-25°C to +50°C	
Part number:	608031-011	Black	
	608031-012	Red (upon request)	
	608031-013	Blue (upon request)	

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.22 - V3 - 17.03.2003 - Released - DefKey : 9768

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com